

U-COMFORT SERIES

The first bathroom fan adaptable to all your needs.

The series of CATA fans are easy-to-install devices to aerate and ventilate the bathroom, as well as to reduce humidity and bad odors.

This series allows to select between 6 different speeds, adjusting in this way the sound level emission.




EXTRA FLAT DESIGN



VERY SILENT




HIGHT ENERGY EFFICIENCY



BACKDRAUGHT SHUTTER INCLUDED

ADJUSTABLE SPEED

Adjustable speed to adapt to all your extraction and sound needs, allowing you to achieve maximum comfort and efficiency in each case.



SIMPLE AND COMPACT INSTALLATION WITH EXTRA FLAT DESIGN

BACKDRAUGHT SHUTTER

It prevents the entry of cold air when the fan is not running and will prevent the entry of bad odors.



MAXIMUM PERFORMANCE, WITH MINIMUM CONSUMPTION




HYGRO VERSION




HYGRO

Maintain an adequate level of Humidity in your bathroom, selecting the maximum humidity you want between 30 and 80% relative humidity.



TIMER

Select the time you need to keep your extractor running after using the bathroom, for its complete air renewal.



Serie U-COMFORT

Energy-efficient. Low-noise.

- Simple and compact installation with Recessed Slim Design,
- **High Performance plastic Housing design and Helico-Centrifugal Impeller.**
- Very Low Noise Level
- Fitted with Low Consumption Motor class B and thermal cut out, ambient temperature max, 40°C
- Rated Voltage 220-240V 50/60Hz.
- Timer and Timer-Hygro models available
- Lots of possibilities to personalize the fan using Accessories to complete the High COMFORT Experience,
- Different Frontal cover designs
- Upgrades through Electronics Systems
- IP-44 and Double Insulation
- Basic Back draught Shutter (included)



HYGRO

STANDARD / TIMER

CODE	MODEL	COLOR	EAN CODE	VERSION	Ø (mm)	Voltage (V)	SPEED (r.p.m)	Input Power (W)	Maximum Airflow (m³/h)	Sound Pressure Level dB(A)	Weight (Kg)	Units per box	110-127V 60Hz on request
HYGRO SERIES													
01200200	UC-10 HYGRO	□	8422248079860	●●●	100	230	2200	8	110	26	0,65	10	√
01201200	UC-10 HYGRO SILVER	■	8422248082594	●●●	100	230	2200	8	110	26	0,65	10	√
01202200	UC-10 HYGRO BLACK	■	8422248082624	●●●	100	230	2200	8	110	26	0,65	10	√
TIMER SERIES													
01200100	UC-10 TIMER	□	8422248079853	●	100	230	2200	8	110	26	0,65	10	√
01201000	UC-10 TIMER SILVER	■	8422248082587	●	100	230	2200	8	110	26	0,65	10	√
01202100	UC-10 TIMER BLACK	■	8422248082617	●	100	230	2200	8	110	26	0,65	10	√
STANDARD SERIES													
01200000	UC-10 STD	□	8422248079846	●	100	230	2200	8	110	26	0,65	10	√
01255000	UC-10 STD SILVER	■	8422248082570	●	100	230	2200	8	110	26	0,65	10	√
01256000	UC-10 STD BLACK	■	8422248082600	●	100	230	2200	8	110	26	0,65	10	√



STANDARD In combination with light, fans switches on.



TIMER Electronic timer adjustable from 3 to 15 minutes.



HYGRO Adjustable humidity detector from 40% to 95%, and adjustable electronic timer from 0 to 15 minutes.



SPEED REGULATION Speed adjustable from 1000 to 2200 RPM.

